

Sentinel Pro

SEP 1000 ER (with BB SEP 36-B1)

INPUT	
Rated power	1000 VA
Voltage	220-230-240 Vac
Voltage tolerance	140 Vac < Vin < 276 Vac @50% LOAD / 184 Vac < Vin < 276 Vac @ 100% LOAD
Frequency	50/60 Hz
Frequency tolerance	50 Hz ± 5% / 60 Hz ± 5%
Power factor	> 0.99
Current distortion	≤7%
BY PASS	
Voltage tolerance	180 - 264
Frequency tolerance	Frequency selected (from ±0.Hz to ±5Hz configurable)
Number phases	1
OUTPUT and INVERTER OUTPUT	
Rated power	1000 VA
Active power	800 W
Number phases	1
Crest factor (Ipeak/Irms)	3 : 1
Waveform	Sinewave
Frequency	Can be selected: 50 Hz or 60 Hz or self-learning
Voltage distortion with distorting load	< 4%
Voltage distortion with linear load	< 2%
OVERLOAD TIMES	
100% < Load < 110%	2 minutes
125% = Load < 150%	5 seconds
Load > 150%	1 second
BATTERIES	
Type	VRLA AGM lead, maintenance-free
Typical recharge time	N. A.
ENVIRONMENTAL	
Altitude max	6000 m
Colour	Black
Communication	USB / DB9 with RS232 and contacts / Slot for communication interface
Safety compliance	EN 62040-1 and directive 2006/95/EL
EMC conformance	EN 620040-2 category C2 and directive 2004/108/EL
Accessories provided	Power cable, serial cable, USB cable, safety manual, quick start, software on CD-ROM
Protection rating	3
Surge capability	300 joule
Marks	CE, GS/NEMKO
Line-Interactive/Smart Active efficiency	98%
Noise	< 40 dBA @ 1 m
Operating temperature	0°C / +40°C
Relative humidity	< 95% not condensed
DATA	
Weight	UPS 7 Kg Battery Box 63Kg
Dimensions (h w d)	158x422x235 mm & BB SEP 36-B1 215x655x630